

CLICK Moduleo® Select Click

Product Information

Level of use	EN 685	23 - 32
Total thickness	EN 428	ca. 4.50mm
Wear layer	EN 429	ca. 0.40mm
Wear layer PUR treatment		Protectonite®
Total weight g/m ²	EN 430	ca. 7.710

Size and Packing

Planks A	EN 427	19.1 x 131.6cm
Tiles A	EN 427	32.4 x 65.5cm
Box planks A	7 pcs/box	1.76m ² /box
Box Tiles A	7 pcs/box	1.49m ² /box

Test Results


Inflammability	EN 13501	Bfl-S1
Scratch resistance	EN 660-2	Class T
Squareness and straightness	EN 427	≤ 0.25mm / ≤ 0.35mm

Slip Resistance

	DIN 51130:2010	BS 7976-2:2002	
	Ramp method	Dry (PTV's)	Wet (PTV's)
Embossing 24	R10	61	34
Embossing 36	R10	67	32
Embossing 40	R10	67	34
Embossing 46	R10	67	33
Embossing 28	R9	68	34

Residual indentation	EN 433	≤ 0.10mm
Furniture leg resistance	EN 424	No cracks, no damage
Curling	EN 434	≤ 2mm
Electrical resistance	EN 1081	≤ 10 ⁹ Ohm
Dimensional stability	EN 1081	Norm: ≤ 0.25% Result: < 0.05%
Heat insulation	EN 12524	0.25w/(m.K)
Thermal resistance R	ISO 8302	not available yet
Electrostatic performance	EN 1815	< 2kV
Fomaldehyde group	EN 717-1	E1
Acoustic insulation	ISO 717-1	4dB
Castor chair resistance	EN 425	No damage to wearlayer, no delamination
Stain resistance	EN 423	Very good
Light fastness	ISO 105 B02	≥ 6
Underfloor heating	EN 12524	Suitable, max 27°C
Resistance to chemicals	EN 423	Very good
Warranty		15 years

The warranty covers manufacturing defects and premature wear in the event of normal use.



Protectonite PU



Scuff and stain resistant



Water resistant



Natural look and feel



Soundproof

