



The unique studded appearance and feel brings new comfort, with excellent acoustic properties and cigarette burn resistance. Ideal for use in corridors, circulation (heavy pedestrian traffic) areas, airports, restaurants, bars, reception areas, offices and waiting rooms.

Specification

Format	Tiles	
Dimensions	500mm x 500mm	(EN427)
Thickness*	2.5/4mm	(EN428)
Weight	3.5/5.8kg/m ²	(EN430)

*Overall thickness includes studs

MRB 4 mm - for heavy duty areas
MRB 2.5 mm - for light to medium duty areas
(See overleaf for stock availability).

A co-ordinating range of accessories including stair nosings, trims, risers and skirtings are available in selected colours.

Performance

Electrical resistance	> 10 ¹⁰ ohms	EN1081
Abrasion	Pass	EN425
	Suitable	EN424 (furniture leg test)
Indentation	≤0.20/≤0.25mm	EN433
Flexibility	Pass	EN435
		(20mm mandrel)
Dimensional stability	<0.4%	(EN434)
Colour fastness	>6	(BS EN 20105)
Flame spread	Class B1	(DIN 4102)
Sound absorption	8dB/15dB	(ISO 140-8)
Thermal insulation	m ² ·k/w	(DIN 52612)
Hardness	≥Shore A 80±5	(ISO 7619)
Cigarettes	≥4	EN1399

Altro Mondopave has excellent resistance to cigarette burns. Light colours may show slight surface staining

Classification (2.5mm)	Class 32/41
Classification (4mm)	EN685 (EN12199) Class 34/43 EN685 (EN12199)

Warranties

Warranty 5 years
(subject to conditions on warranty form which is available from Altro).

Life expectancy 10/15 years

Chemicals and Staining - Tested to EN423

Resists	Common dilute acids, alkalis and many alcohols
Caution	Oil-based compounds can cause deterioration on sustained contact* .

*Please consult Altro Technical Services.

Chemical spillages should always be removed immediately to protect the floor. For areas liable to chemical spillages, please consult Altro for technical advice.

N.B. More information on performance and standards is available in the Altro flooring and walling brochure or at www.altro.com

Colour Choice

The colour of Altro rubber flooring should be carefully chosen with expected traffic conditions in mind and protective measures, such as the use of barrier matting, should be taken wherever possible.

versatile collection / rubber flooring Altro Mondopave



altro

our promise to deliver



the highest quality products & services



Resilient Flooring Range of the Year
(6th year running)

Materials of Composition

Calendered and press-vulcanised synthetic rubber with mineral aggregates, stabilising agents and pigments. This material is recyclable.

Recommended Cleaning Methods

Altro Mondopave is supplied with a matt finish. To retain the appearance, protect flooring from other trades and maintain with a protective dressing such as AltroGloss™ 211 or similar, or spray buff. Do not polish when in wet installations. Do not wash in direct sunlight. Refer to Altro rubber flooring maintenance instructions for comprehensive cleaning advice, visit www.altro.com or telephone 01462 707600.



Installation and Maintenance

All installations in accordance with Code of Practice BS 8203:2001, and Altro rubber installation instructions.

Subfloor	As Code of Practice, with effective DPM where necessary
Adhesives	As recommended in Altro rubber flooring installation instructions, the Altro price list or visit www.altro.com

N.B. Failure to install and maintain Altro flooring in accordance with Altro's instructions can affect the performance of the product. Floors should be protected from other trades and thoroughly cleaned before handover.

Altro Flooring and Walling Ranges

Products include safety flooring, smooth flooring, resin systems, Mondo rubber, sports flooring, hygienic wall coatings, hygienic PVCu walling and ceiling systems, hygienic doorsets, decorative wall coatings and protective wall coatings. For more information ask for the Altro Flooring and Walling Solutions brochures appropriate to your industry sector, or visit www.altro.com

Sample Specification

The rubber flooring to be Altro rubber flooring Mondopave thickness 2.5/4mm, size 500mm x 500mm colour (...). All flooring to be laid according to Altro's manufacturer's instructions with recommended adhesives.

NBS model specification is available for downloading on www.altro.com or telephone 01462 707600.

Prior to specification please ensure you are referring to the most recent sample card.



To obtain individual samples use the SampleExpress service. Please quote the product range and product name/number. Larger samples are also available but may take a few days.

Explore Light. Explore Colour.
Explore Mood. At www.altro.com

explore altroism at www.altro.com