

QUALITY DATE: **24/02/2011**  
ORDER CODE REPLACES: 21/12/2010

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD  
  
PILE COMPOSITION  
FIBRE BRAND  
WOOLMARK  
ANTISOIL  
MOTHPROOF  
  
PRIMARY BACKING  
  
SECONDARY BACKING  
  
PILE WEIGHT (±) gr/m<sup>2</sup>  
EFFECTIVE PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (± 15%) gr/m<sup>2</sup>  
  
EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm  
  
REPEAT TUFTING DESIGN (±) mm  
REPEAT PRINTING DESIGN (±) mm  
  
ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER

UPEC n°  
CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION  
CLASSIFICATION BS7131

EN 13501-1

BS 4790

**OASIS SB/DLN OAS**  
**OAS**

± 400 & 500  
COLLECTION  
1/4" BERBER LOOP PILE

FLOCK DYED

WO  
WOOLMARK  
MEDIUM DUTY RESIDENTIAL

✓

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.030  
±  
± 2.330

± 5,4  
± 9,0  
± 56.880  
± 15,80  
± 36,00

±  
±

± 25  
PILE IN

✓

✓

✓

STATIC CONTROL

✓

✓

9D6D2B2E

20975

CL. 22  
Domestic General/Medium



LC2 LC2

Cfl-s1 Cfl-s1

LOW RADIUS

QUALITY

DIMENSIONAL STABILITY

EN 986

OASIS SB/DLN OAS

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

±

SOUND ABSORPTION

(±)

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

EN ISO 11654

±

THERMAL RETENTION

(±) m<sup>2</sup>/KW

ISO 8302

± 0,119



TOG rating

(±)

± 1,19

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

<

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 4-5

RUBBINGFASTNESS WET

ISO 105 X12

≥ 4-5

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 4-5

WATERFASTNESS STAINING

ISO 105-E01

≥ 4-5

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SB/DLN 400		SB/DLN 500
152	SAHARA 2	152
182	RUM 2	182
222	DEER	222
232	CARAMEL	232
242	BISCUIT	242
252	MAGNOLIA 2	252
452	SAND 2	452
462	HEMP 2	462
472	ANGORA 2	472
822	SLATE 2	822
852	MOONBEAM 2	852
892	SNOW 2	892

SB/DLN 400	SB/DLN 500
(12)	(12)



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE