

**SOFTWALK**

**Polyurethane rebond carpet cushion with a tan, printed reinforced backing and blue facing**

<b>Application</b>	Domestic use by stretch fit where underfoot comfort is paramount	
<b>Roll size</b>	11m x 1.37m / 15m <sup>2</sup>	12yd <sup>2</sup> x 54" / 18yd <sup>2</sup>
<b>Roll weight</b>	14.0kg	31lb
<b>Square weight</b>	0.9kg/m <sup>2</sup>	27oz/yd <sup>2</sup>
<b>Thickness</b>	9mm	0.350"
<b>Packaging</b>	Silver coloured wrap with blue print	



**PERFORMANCE TO BS 5808<sup>①</sup>**

<b>1 Classification</b>	BS5808:1991	L/U
<b>2 Work of compression [WOC]</b>	BS4098:1975-100kPa	typically 160J/m <sup>2</sup>
<b>3 Retention of WOC after dynamic loading, 1000 hits</b>	BS4098:1975-100kPa	typically 85%
<b>4 Loss in thickness under static loading</b>	BS4939:1987	less than 5%
<b>5 Loss in thickness under dynamic loading</b>	BS4052:1987	typically 5%
<b>6 Resistance to cracking</b>	BS2576:1986	Pass

**ADDITIONAL DATA**

<b>1 Reduction of transmitted impact noise</b>	BS EN ISO 140 Pt 8:1998 BS EN ISO 717 Pt2:1007	39dB
<b>2 Effects of ignition source, hot metal nut</b>	BS4790:1987 / BS5287:1988	Low radius/Pass <sup>①</sup>
<b>3 Thermal resistance</b>	BS4745:1980	2.1 Tog

<sup>①</sup> Gates laboratory result

**The Gates Rubber Company Limited Edinburgh Road Dumfries DG1 1QA United Kingdom**  
**Home sales Tel 08457 600400 Fax 01387 250542**  
**Export sales Tel +44(0)1387 240821 Fax +44(0)1387 250542**



Tredaire products do not contain, and are not manufactured using Formaldehyde, CFCs, Heavy Metals, other toxic materials or products from endangered species.  
All information contained in this document is correct at the time of going to press. It is the property of Gates and may not be reproduced in whole or in part without the consent of The Gates Rubber Company Limited.