

Product Specification Unnatural flooring

Inflammability	IMO FTPC Part 5	Low Flame Spread
Slip resistance	DIN 51130	R10

Product information

Classification	CSTB	U3SP3
Material	-	97% vinyl, 2% polyester, 1% glass fibre
Total thickness	EN 429	With backing, 3mm
Total weight	EN 430 EN 430	With backing 3000 g/m ² Tiles 4000 g/m ²
Width	EN 426	200 cm
Standard Length	-	ca. 50 m
Weight of standard roll	-	340kg
Tiles	EN427	50cm x 50cm

Technical information

Inflammability	IMO FTPC Part 5	Low Flame Spread
Fire Standard	France UK EN ISO 13501 EN ISO 9239-1 EN ISO 11925-2	Class M3 BS 4790
Smoke Density	ASTM E 662	Flaming exposure, Dm 293 Non-flaming exposure, Dm 373
Radiant Panel	ASTM E 648	0.84 W/cm ² Type 1 (NFPA 101)
Thickness Loss	EN 425 SFS 3185	0.2mm
Dimensional Stability	EN 434	< 0.03%
Colour Fastness	ISO 105-B02	>6
Impact Sound	ISO 140-8	Lw = 19 dB
Static Electricity	ISO 1815	Ant-Static
Castor chair resistance	EN 425 DIN 54324	>25,000 cycles
Curling	EN 434	0mm
Slip Resistance	BS 7976-2	