

## Karndean Designflooring

n5Plus



### Versilay

By Karndean Designflooring

#### Detailed description

##### Features:

- Free floating, dual underlay system, providing a smooth surface ready to receive new floor coverings.
- Provides acoustic and thermal insulation properties.
- Small irregularities in concrete or timber sub-floors, such as joints and cracks, are smoothed-out.

##### Components:

###### - Top Board:

- 4 mm fibreboard E1 (with interactive adhesive pre-glued backing).
- Density: 820 kg/m<sup>3</sup>.

###### - Base Board:

- 3 mm Aluminium polystyrene backing (foam with vacuum metallized aluminium layer) glued to 3 mm fibreboard E1 (with interactive adhesive pre-glued top).
- Density: 820 kg/m<sup>3</sup> (fibreboard); 25 kg/m<sup>3</sup> (aluminium polystyrene backing).

##### Usage:

- Domestic and commercial installations.
- Not recommended for use in areas that are subject to high levels of moisture and free water.

#### Options

##### Thickness:

10 mm (overall).

##### Board size:

600 x 1200 mm.

##### Density of composed product:

585 kg/m<sup>3</sup>.

##### Acoustic Noise Reduction:

- EN-ISO 717-2.
- Lm= 21db.

Thermal resistance:

R-value: 0.13 m<sup>2</sup>K/W.

**Product specification**

Manufacturer

- Name: Karndean Designflooring
- Web: [www.karndean.co.uk](http://www.karndean.co.uk)
- Email: [commercial@karndean.co.uk](mailto:commercial@karndean.co.uk)

Product reference                      Versilay