



[spacia]access

Fast, simple, effective flooring solutions
for commercial environments.

in business

For more than 40 years, Amtico International has been the world's leading supplier of premium, resilient flooring and the enduring choice of style-aware designers and specifiers. Our unique understanding of interiors and trends has inspired us to develop Spacia.

Spacia is a beautifully simple, stylish flooring collection of contemporary stones and woods, created, approved and quality tested by Amtico International's team of experts.

Ideally suited for today's commercial applications.



S-AX5004 Honey Oak

Why choose [spacia]access

- Requires NO permanent adhesive
- Fast installation and removal
- Ideal for raised access floor systems.
- 10 year commercial warranty against wear-out.
- Easy to adapt in area size and shape.
- Choose from 4 stones and 8 woods.
- Increased scratch and scuff resistance.
- Low maintenance.

solution [spacia] access

Specifically designed to be installed without the need for adhesive, Spacia Access provides the ideal solution for areas with raised access floor, making it the perfect alternative to carpet tiles. Spacia Access offers versatility for many commercial applications whether semi-permanent installations for offices, promotional areas in department stores, supermarkets, exhibitions, or permanent installations with the flexibility to easily adapt in area size and shape as needs dictate.



Spacia Access provides some of the highest levels of durability and acoustic performance, is fast to install (ideal for overnight refurbishment programmes) and requiring no adhesive, tiles are effortless to remove and replace. Spacia Access also has the added benefit of being easy to maintain and offer higher levels of hygiene when compared to carpet tiles and many other alternative floor types.





S-AX5014 Traditional Oak



S-AX5007 Antique Oak

[spacia] access - woods



S-AX5004 Honey Oak



S-AX5014 Traditional Oak



S-AX5006 Warm Cherry



S-AX5016 Bleached Elm



S-AX5007 Antique Oak



S-AX5017 Warm Teak



S-AX5008 Walnut Chocolate



S-AX5018 Pale Ash

Spacia Access wood products are bevelled as standard and are available in tick finish only.

Wood Sizes: 500mm x 500mm (19.7" x 19.7") & 183mm x 1219mm (7.2" x 48")
Tile Thickness: 5mm (200mil)

S-AX5004 Honey Oak



S-AX5065 Ceramic Light & S-AX5066 Ceramic Dark



S-AX5066 Ceramic Dark


[spacia] access - stones




S-AX5052 Travertine




S-AX5052 Travertine



S-AX5051 Classic Warm Stone



S-AX5065 Ceramic Light



S-AX5066 Ceramic Dark

Spacia Access stone products are bevelled as standard and are available in ceramic finish only.

Stone Sizes: 500mm x 500mm (19.7" x 19.7")

Tile Thickness: 5mm (200mil)

Guidelines for All Floor Sizes

Installation Instructions for the laying of Spacia Access tiles

Pre-Installation

Check the quantities, colour and batch numbers before beginning the installation. Tiles, tackifier and sub-floor must be allowed to stabilise to a constant temperature between 18°C - 27°C for a period of at least 24 hours before, during and after installation. Tiles must be stored flat.

General Floor Preparation

The sub-floor must be hard, smooth, dry, free from undulation and level. As per BS8203 the floor should only be installed if the base is sufficiently dry to show a hygrometer reading less than 75% relative humidity (RH). An appropriate smoothing compound may be used where necessary.

Concrete Floors

Existing concrete floors must be cleaned of all paint, grease, wax and any other foreign matter. Any surface irregularities or imperfections must be addressed prior to installation.

Ceramic/Terrazzo/Stone Floors

Inspection should be carried out to ensure that all tiles are securely fixed. Any loose tiles must be removed and along with grout lines must be filled and levelled.

Existing Resilient Floors

Spacia Access tiles can be installed over existing resilient flooring. Inspection should be carried out to ensure that all tiles are securely fixed. Any loose tiles must be secured.

Wood Floors

Plywood, hardwood and particle board used as a sub-floor must be stable and of a flooring grade and installed to manufacturers recommendations. All joints should be filled and any rough areas sanded smooth.

Raised Access Floors

These should be clean, smooth, level and dry. Tile joints should not coincide with the joints of the raised panels.

Installation

An appropriate tackifier should be applied to the substrate prior to installation, and should be applied by either brush or roller. The tackifier should be allowed to dry to a clear tacky film, normally around 15 minutes, before placing the tiles into position.

When placing perimeter tiles into position, it is recommended they are cut to size ie they fit neatly into place rather than requiring bending and forcing into place.

On completion of the installation, the floor should be rolled with a suitable 45 kg roller in two directions to ensure good contact between tiles and tackifier.



Guidelines for All Floor Sizes

All floors should be swept and dust mopped daily, following which soiling and marking can be removed using the appropriate method described below. In most cases, manual mopping should be adequate, but spray cleaning may be required to remove heavier surface marking.

Entrance matting should be used to trap grit and dirt. Felt pads or furniture cups should be used under all furniture legs. Do not drag or slide objects across the floor.

Warning signs should be used to advise people that cleaning is in progress.

Spacia Access floors are not suitable for cleaning using a scrubber-drier.

Dressings should not be applied to Spacia Access floors.

Daily Sweeping and Dust Mopping

Pick Up litter and thoroughly sweep the floor area.

Pick up debris with dustpan and brush or vacuum.

Vacuum walk-off mats and crevices at entrance(s).

Manual Mopping

Manual mopping will remove soiling and the majority of surface marking. Mopping must be carried out using a damp mop only.

Prepare a correctly diluted solution of neutral detergent

Using a two-bucket mopping system, apply a solution using a well wrung mop.

Rinse the mop frequently and change the solution as necessary.

Spray Cleaning

Spray cleaning can be used for light soil removal and removal of scuff marks. If the floor is heavily soiled it may be appropriate to carry out an initial manual clean with mop and bucket.

Pour correctly diluted neutral cleaner or cleaner maintainer into a spray container.

Apply a fine mist of liquid on to an area of approximately 2 square metres at a time.

Use a rotary buffing machine (approx. 450rpm) fitted with a red 3M nylon pad (or equivalent).

DISCLAIMERS WITH REFERENCE TO INSTALLATION AND USE OF SPACIA ACCESS FLOORS

1. In those areas subject to potentially large changes in temperature - for example floors exposed to direct sunlight, particularly in rooms without air conditioning, it is recommended that Amtico HT Adhesive is used to install tiles.
2. Installation temperature should be constant between 18 - 27°C for 24 hours before, during and 24 hours after installation has been completed. Tiles should also be conditioned at this temperature for a minimum of 24 hours before installing.
3. The product should not be installed in unheated rooms or exterior locations.
4. The surface temperature of the tile should not exceed 27°C as temperatures above this can cause discoloration.
5. The product is not suitable for use with under-floor heating.
6. Overspray from furniture polish and other spray products should be avoided as they can cause slippery floors.
7. Rubber-backed carpets and rugs etc may cause staining and should be checked for

Also from Amtico International



Amtico Internationals forty years of experience in the flooring industry and unique understanding of customers needs has led to the development of Spacia for the home and for business: a simple stylish collection of woods and stones for everyday living and working.

[spacia]access - Technical Data

Standard	Reference	Result
Manufacturing Standard	EN649 ASTM F1700-99	Pass Pass
Wear Group Classification	EN685	23,33,42
Abrasion Resistance	EN660-2	Group T
Slip Resistance	DIN 51130 ASTM D2047-99 EN13893 CLASS DS	R9 >0.5 (dry coefficient of friction) ADA Compliant
Residual Indentation	EN 433 ASTM F1700-99	<0.1mm Pass
Chemical Resistance	DIN 51958 ASTM F925	Excellent Excellent
Light Stability	ISO 105 B02 ASTM F1515	6 or better Exceeds requirements
Dimensional Stability	EN434 ASTM F1700	<0.25% Exceeds Requirements
Flexibility	EN435 ASTM F37	Pass Pass
Flammability/Smoke Emissions	EN13501-1	B _{FL} S1
Wear Layer Thickness	EN429	0.55mm
Castor Chair Resistance	EN425	Pass
Sound Reduction	ISO 140-8	9dB

Amtico International	General Numbers	Request a Sample
UK Head Office Kingfield Road, Coventry CV6 5AA	Tel: +44 (0) 24 7686 1400 Fax: +44 (0) 24 7686 1552	Rapid Sample Service Tel: +44 (0) 8703 50 40 90 Fax: +44 (0) 8703 50 40 91
UK & European Sales Solar Park, Southside Solihull, West Midlands B90 4SH	Tel: +44 (0) 121 745 0800 Fax: +44 (0) 121 745 0888	
USA Atlanta 6840 Roswell Road, Atlanta, GA 30328	Tel: +1 404 267 1900 Fax: +1 404 267 1901	Tel: +1 800 268 4260
Germany Im Taubental 11, 41468 Neuss-Grimlinghausen	Tel: +49 (0) 2131 359 16 0 Fax: +49 (0) 2131 359 16 50	Tel: +49 (0) 2131 359 16 0
France 25 rue de Sèvres, 92100 Bologne, Paris	Tel: +33 (0) 1 55 38 95 70 Fax: +33 (0) 1 55 38 95 71	Tel: +33 (0) 1 55 38 95 70
Sweden Box 6057, Skälbyvägen 16, S-175 06 Järfälla	Tel: +46 (0) 8 584 233 24 Fax: +46 (0) 8 584 233 30	Tel: +46 (0) 8 584 233 24
Australia Unit 3/31 Gibbs Street, Chatswood, NSW 2067	Tel: +61 (0) 2 9415 0200 Fax: +61 (0) 2 9417 3344	Tel: +61 (0) 2 9415 0200

International Enquiries

For overseas customers, please contact your nearest Amtico International office

Samples and Information www.spaciafloors.com

To keep up-to-date with the very latest about Spacia, visit our website. Simply go to www.spaciafloors.com to find everything from details of our newest product launches and the brightest design ideas, advice on installation, cleaning and maintenance.

Every effort is made to achieve accurate colour reproduction of products in this brochure, however printing limitations can be misleading. Selection of colours should be made from actual samples. Samples are small pieces cut from standard tiles. They give only a general indication of colour and do not necessarily show the complete design. Colour and shading can vary slightly from batch to batch, and it is not possible to guarantee that the colour of the sample will exactly match the material supplied. The policy of the Company is one of continuous development and improvement and the right is reserved to add or delete from the range or change patterns without prior notification.

07/08

www.spaciafloors.com