

TOTAL FLOOR CARE LTD

Stripping & Sealing of Dalsouple Rubber Floors

Dalsouple have nominated Total Floor Care Ltd as their Service Partner to offer a nationwide cleaning and maintenance service. After the floor has been installed it should be swept clean. **No wet cleaning should take place for 7 days, until the adhesive has fully cured (in accordance with the adhesive manufacturer's instructions).**

Health & Safety for PRO 1

It is essential to read and follow the safety instructions on the label prior to use.

Skin: Avoid contact with skin. May cause burns, wear protective gloves and clothing.
Avoid contact with eyes and face, wear safety glasses. The product should not be ingested. Will cause corrosive damage to mouth, throat and gastrointestinal tract. Keep away from food or sources that could be ingested.

KEEP OUT OF REACH OF CHILDREN

Stripping the Floor

Clear the area, protect any stainless steel, woodwork etc that may be effected by the stripping process.

Dilute the **PRO 1** (ten parts cold water to **one** part **PRO 1**) Mop diluted solution on the floor and leave for approx. 5 - 10 minutes. Do not allow the floor surface to dry out. Use the scourer to remove any contaminates. **Do not scrub the floor too hard, it may scratch the rubber**, use more dilute **PRO 1** as required. After approx. 5 – 10 minutes mop up the residue and then rinse the floor with cold water thoroughly. **Allow the floor to dry.**

Sealing the Rubber

When the floor is dry. Apply two or more coats of **PRO 3** (well shaken) to the surface using the applicator (remove loose bits of fluff). Pour neat to the applicator, wiping on the floor in thin even strokes allowing the first coat to dry **thoroughly**, before applying the second coat at right angles to the first.

Maintaining the Rubber Floor

The surface is maintained with **PRO 4**.

All floor surfaces must be totally free from dust before the cleaning programme starts.

DAMP MOPPING: Dilute half a cupful (100ml) of **PRO 4** in 5 litres of water, apply to the floor, then leave to dry.

PRO 4 AS A FLOOR FINISH: Apply two **neat coats** evenly on the floor surface allowing the first coat to dry thoroughly, before applying the second coat at right angles to the first. Leave to dry.

Daily maintenance will vary according to the traffic conditions.

Health & Safety PRO 1 is a corrosive material, all labels and instructions should be read carefully before use. Total Floor Care will not be liable for any damage or injury.