

SENSATION CONSTRUCTION SPECIFICATION

CONSTRUCTION PILE CONTENT WIDTH SUITABILITY	BS4407 BS3655	Tufted Cut Pile Carpet 100% Luxelle PP 4 metre & 5 metre Extra Heavy Domestic / Medium Contract
ROLL SIZE		Standard 25m or 30m (Special sizes can be supplied, please allow extra time for delivery)
PRIMARY BACKING SECONDARY BACKING		Woven Polypropylene Woven Secondary
PILE HEIGHT TUFT DENSITY PILE WEIGHT TOTAL CARPET WEIGHT TOTAL CARPET THICKNESS	BS 4223/ISO 8543 BS 4223/ISO 8543 BS 4223/ISO 8543 BS 4223/ISO 8543 BS 4051/ISO 1765	12.5mm 142,600 tufts/m ² 1966gms/m ² (58oz/yd ²) 2746gms/m ² 15.5mm
FLAMMABILITY METHENAMINE PILL TEST		Pass
COLOUR FASTNESS LIGHT FASTNESS WET FASTNESS SHAMPOO FASTNESS	BS 1006 above Grade 6 on all colours BS 1006 above Grade 4/5 on all colours BS 1006 above Grade 4/5 on all colours	
BIOLOGICAL ATTACK	Insect and rot proof	
THERMAL RESISTANCE (Tog Value)	BS4745/ISO 5085-1	1.7 Tog
WIRA ABRASION RESISTANCE STATIC LOADING DYNAMIC LOADING TUFT ANCHORAGE		Exceeds 50,000 rubs 20.5% Thickness Loss after 24 hours recovery 28.8% Thickness Loss after 1,000 impacts Above 1.0kg

All specifications are subject to normal manufacturing tolerances.

GENERAL INFORMATION

Installation

In all contract locations an 'all over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. If exact colour matching is required for a quantity order, please state this point clearly when ordering.

Maintenance

To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. An upright vacuum with beater bar and brush is recommended for use with cut pile carpets. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear. These areas will appear lighter or shaded in comparison to the less frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Similarly Pile Reversal (or watermarking) is a phenomenon that can affect all cut pile carpets and as such is not accepted as a manufacturing fault.

Matching

This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

Important

Minimum order length is 1.5 metres.



GREENWOOD & COOPE LTD

BROOKHOUSE MILL, GREENMOUNT, BURY, LANCASHIRE BL8 4HR TEL: 01204 880234 FAX: 01204 880700

E-MAIL: info@cormarcarpets.co.uk WEBSITE: www.cormarcarpets.co.uk

May 2002

