



SAFETY DATA SHEET STYCCOBOND F60

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME STYCCOBOND F60

INTERNAL ID SBF60/9

APPLICATION Flooring Adhesive

SUPPLIER F.Ball and Co.Ltd.,
Churnetside Business Park,
Station Road.,
Cheddleton,
Staffordshire ST13 7RS
For technical and non-emergency call:
phone: 01538 361633.
For advice on medical emergencies,
fires, spillages or chemical hazards
phone: +44(0) 870 190 6777
Fax: 01538 361622
E-Mail: mail@f-ball.co.uk

2 HAZARDS IDENTIFICATION

Highly flammable. Vapours may cause drowsiness and dizziness. Irritating to skin. Possible risk of harm to the unborn child. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xn;R48/20. Rep 3;R63. Xi;R38. F;R11. N;R51/53. R67.

ENVIRONMENT

Solvent contamination of drains, surface waters and land. VOC emissions to air. Potential fire and explosion hazard.

HUMAN HEALTH

Contains a substance with possible risk of harm to the unborn child.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ACETONE	200-662-2	67-64-1	1-5%	F;R11 Xi;R36 R66 R67
BUTANONE	201-159-0	78-93-3	1-5%	F;R11 Xi;R36 R66 R67
CYCLOPENTANE	206-016-6	287-92-3	1-5%	F;R11 R52/53
HEPTANE	205-563-8	142-82-5	10-30%	F;R11 Xn;R65 Xi;R38 R67 N;R50/53
HEXANE-norm	203-777-6	110-54-3	0.5-1%	F;R11 Repr3;R62 Xn;R65,R48/20 Xi;R38 R67 N;R51/53
METHYLCYCLOHEXANE	203-624-3	108-87-2	1-5%	F;R11 Xn;R65 Xi;R38 R67 N;R51/53
PENTANE	203-692-4	109-66-0	0.5-1%	F+;R12 Xn;R65 R66 R67 N;R51/53
ROSIN	232-475-7	8050-09-7	0.1-0.2%	R43
TOLUENE	203-625-9	108-88-3	35-50%	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

A solution of resins and elastomers in a blend of organic solvents.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. DO NOT induce vomiting. Get medical attention immediately.

STYCCOBOND F60**SKIN CONTACT**

Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray should be used to cool containers.

UNUSUAL FIRE & EXPLOSION HAZARDS**HIGHLY FLAMMABLE****SPECIFIC HAZARDS**

In case of fire toxic gases/vapours may be formed.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

Evacuate non-essential personnel from the spill area. Do not smoke, use naked flames or other sources of ignition. Take precautionary measures against static discharge and arcing from electrical equipment. Avoid inhalation of vapours and contact with skin and eyes. Use protective gloves, goggles and suitable protective clothing. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Dam and absorb spillage with sand, sawdust or other absorbent. Collect spillage in containers, seal securely and deliver for disposal as hazardous waste.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Observe workplace exposure limits and minimise the risk of inhalation of vapours and mist. Risk of vapour concentration on the floor and in low-lying areas. Do not use in confined spaces without adequate ventilation and/or respirator. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

STORAGE PRECAUTIONS

Stored in tightly closed original container in a cool, dry well ventilated place at a temperature between 5 deg C and 30 deg C. Protect against physical damage and/or friction. Keep away from heat, static or electrical sparks, open flame and direct sunlight. Avoid contact with oxidising agents. Keep separate from food, feedstuffs, fertilisers and other sensitive material.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3
BUTANONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)
HEPTANE	WEL	500 ppm			
PENTANE	WEL	600 ppm	1800 mg/m3		
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	100 ppm(Sk)	384 mg/m3(Sk)

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours. Explosion-proof general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use a respirator suitable for organic vapours. Consult respirator manufacturer for specific advice.

HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.

STYCCOBOND F60**EYE PROTECTION**

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

PERSONAL PROTECTION

Always check applicability with your supplier of protective equipment.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Viscous liquid		
COLOUR	Brown		
ODOUR	Organic solvents.		
RELATIVE DENSITY	0.85-0.89 approx @20 degC	VOLATILE BY VOL. (%)	74 w/w approx
pH-VALUE, CONC. SOLUTION	Not applicable	VISCOSITY	8000 - 10,000 cps @ 20 degC
FLASH POINT (°C)	-18 approx CC (Closed cup).		

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Oxidising materials.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION**INHALATION**

Harmful by inhalation. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

INGESTION

Irritating. May cause nausea, stomach pain and vomiting.

SKIN CONTACT

Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking.

EYE CONTACT

Irritating and may cause redness and pain. Risk of corneal damage.

SPECIFIC EFFECTS

Contains a substance with possible risk of harm to the unborn child.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

DEGRADABILITY

The dried product is not readily biodegradable but is inert and not likely to pose an ecological hazard.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Should be disposed of as hazardous waste via a licensed waste operator.

WASTE CLASS

Hazardous Waste Codes: Product: 080409* ; Contaminated empty container 150110*

14 TRANSPORT INFORMATION

STYCCOBOND F60



UK ROAD CLASS	3	UK ROAD PACK GR.	III
PROPER SHIPPING NAME	ADHESIVES	ADR CLASS	Class 3: Flammable liquids.
UN NO. ROAD	1133	HAZARD No. (ADR)	30
ADR CLASS NO.	3	HAZCHEM CODE	3Y
ADR PACK GROUP	III	RID CLASS NO.	3
ADR LABEL NO.	3	UN NO. SEA	1133
CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp	IMDG PAGE NO.	3
RID PACK GROUP	III	EMS	F-E, S-D
IMDG CLASS	3	MARINE POLLUTANT	No.
IMDG PACK GR.	III	AIR CLASS	3
MFAG	See Guide		
UN NO. AIR	1133		
AIR PACK GR.	III		

15 REGULATORY INFORMATION

LABELLING



Harmful



Highly Flammable



Dangerous for the environment

CONTAINS

TOLUENE

RISK PHRASES

R11	Highly flammable.
R38	Irritating to skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63	Possible risk of harm to the unborn child.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S7/9	Keep container tightly closed and in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S24/25	Avoid contact with skin and eyes.
S33	Take precautionary measures against static discharges.
S36/37	Wear suitable protective clothing and gloves.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
P14	Contains ROSIN. May produce an allergic reaction.

16 OTHER INFORMATION

GENERAL INFORMATION

F.Ball and Company Ltd Technical Datasheet.

INFORMATION SOURCES

Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits.

STYCCOBOND F60

REVISION COMMENTS

Section 8 Update - Changes to workplace exposure limits

REVISION DATE 26/09/07

REV. NO./REPL. SDS GENERATED 9

RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R36	Irritating to eyes.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.