

BALL AND YOUNG LTD TECHNICAL INFORMATION

COMFISTEP 8

APT

Suitable For General Domestic Areas

Adds Luxury and Comfort

Easy to Lift and Handle

Recommended Areas of Use	Suitable for general / light domestic areas Domestic installations Areas of medium / low wear	
Top Surface :	Spun bonded non-woven fabric	
Bottom Surface :	Thermoplastic Film	
Nominal Thickness :	8.00 mm	
Nominal Roll Weight :	10.3 Kg	22.7 lb
Weight per unit area:	683 g/M ²	20 oz/yd ²
Roll Length :	11.00 M	36.0 ft
Roll Width :	1.37 M	54 In

BS 5808 : 1991 Test Results - British Standard for Carpet Underlays

End use Classification	BS. 5808	GD/U - L/U
Work of Compression after 1000 impacts	BS. 4098	>100 J/M ²
Retention of Work of Compression	BS. 4098	>50 %
Loss in thickness after Static Loading	BS. 4939	< 10.00 %
Loss in thickness after Dynamic Loading	BS. 4052	< 10.00 %
Resistance to Cracking	BS. 5808 (A)	Pass

BALL AND YOUNG TECHNICAL INFORMATION

COMFISTEP 8

Other Relevant Tests

Thermal Resistance (TOG Rating)	2.3 Tog Estimated
Impact Sound Improvement Index (Tested / rated to BS EN ISO 140-8 /BS EN ISO 717-2)	31 dB Estimated