



B

BROADRIB

Broadrib is a heavy contract fibre bonded floorcovering and can be found in education, universities, libraries, apartment block communal areas, office environments, retail outlets, and public sector buildings. Its wider rib structure compared to Supacord, creates a more defined texture within the carpet.



Specification		Broadrib		10 YEAR WEAR WARRANTY	
Fibre Construction	80% Polypropylene, 15% Polyamide, 5% Recycled Polyester				
Colour Fastness	Light (BS EN ISO 105:B02) >6 Wet Rubbing (BS EN ISO 105:B01) 5 Dry Rubbing (BS EN ISO 105:X12) 5				
Flammability	BS5287 Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char BS EN 13501 Class Cf-l-s1 (Sheet) Class Cf-l-s1 (Tile) Class Cf-l-s1 (Plank)				
Antistatic	Suitable for use in computer rooms				
Impact Noise Reduction	BS EN ISO 140-8:20dB (Sheet) Acoustic Tile - BS EN ISO 140-8:25dB				
Formats	Sheet ● Tile ◆ Plank ▬				
Backing	- Bitumen				
Size	2 metre and 4 metre 500cm x 50cm				
Tiles Per Box	- 20 (5m ²)				
Weight	1020gsm 4020gsm				
Thickness	7.50mm 8mm Acoustic Tile - 12.50mm				




BREEM® 'A+' Rated



H

HOBNAIL

Hobnail is a heavy contract fibre bonded floorcovering and can be found in education, universities, libraries, apartment block communal areas, office environments, retail outlets, and public sector buildings. Ideal in communal areas with a non-directional pattern.




STEEL

LRV 7.45



COBALT

LRV 7.11




CLARET

LRV 7.56



PEBBLE

LRV 8.48




FLINT

LRV 5.32



BLUE

LRV 4.20



APABIAN RED

LRV 4.09



SHERWOOD

LRV 5.51



ANTHRACITE

LRV 3.43




PACIFIC BLUE

LRV 3.35



AZURE

LRV 7.22



GREEN

LRV 5.49




CHARCOAL

LRV 2.01



SEAL

LRV 9.12



AMETHYST

LRV 6.76



PURPLE

LRV 1.78

Specification	Hobnail
Fibre Construction	80% Polypropylene, 15% Polyamide, 5% Recycled Polyester Light (BS EN ISO 105:B02) 6 Wet Rubbing (BS EN ISO 105:B01) 5 Dry Rubbing (BS EN ISO 105:X12) 5
Colour Fastness	BS5287 Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char (BS EN 13501 Class Cf-l-s) (Sheet) Class Bfl-s1 (Tile)
Flammability	Suitable for use in computer rooms
Artistic	Sheet ● Tile ◆
Formats	Bitumen
Backing	50cm x 50cm
Size	20 (5m ²)
Tiles Per Box	4020gsm
Weight	7.20mm
Thickness	8mm