

QUALITY
ORDER CODE

DATE: **23/04/2019**
REPLACES: 29/11/2018

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1

BS 4790

EVITA SB
LEVI

± 400 & 500
COLLECTION
5/64" CUT PILE

PIECE DYED

PA

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.800
± 2.600

± 6,5
± 8,5
± 257.040
± 50,40
± 51,00

±
±

± 25
PILE IN

✓
✓
✓

✓

✓

4CB55DDD

Cl. 32
Commercial General



LC5



Cfl-s1



QUALITY

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,09

TOG rating

(±)

± 0,9

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤ 2000



LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE

CE
19
EN 14041
DOP 1038-126377
NB 1611



LANO NV - Venetiëlaan 33
B-8530 HARELBEKE
Floor carpets to use in
buildings

RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE
FROM

AVAILABLE
FROM

COLOURS

<u>SB 400</u>	LEVI	<u>SB 500</u>
0020	LAVENDER	0020
0050	CROCUS	0050
0060	HEATHER	0060
0240	CREAM	0240
0260	CAMEL	0260
0410	LEATHER	0410
0750	SKY	0750
0780	STEEL	0780
0790	MIDNIGHT	0790
0810	CHARCOAL	0810
0820	SLATE	0820
0830	ASH	0830
0850	MOONBEAM	0850
0870	SILVER	0870
0880	PEARL	0880
0890	SNOW	0890

<u>SB 400</u>	LEVI	<u>SB 500</u>
---------------	-------------	---------------



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

(16)

(16)