

CANNES

Construction	: Tufted 1/10 cut pile
Plie Material	: Faux Silk
Secondary Backing	: Luxury Backing
Pileweight	: ca. 1.85 kg/ sq mtr +/- 7.5%
Totalweight	: ca. 2.60 kg/ sq mtr +/- 7.5%
Carpet Thicknes	: ca. 14 mm +/- 7.5 %
Usage Classification EN 1307:2014	: Class 33 / Heavy Commercial use
Comfort rating EN1307:2014	: LC 5
Static Electricity Charge	: Anti static
Light ISO 105 B02:2013	: 5-6
Rubbing - Dry ISO 105 X12	: 4-5
Rubbing - Wet ISO 105 X12	: 4-5
Water ISO 105 E01 : 2013	: 4
Water Stains EN1307/EN15115	: 4-5
TOG rating	: 1.64
Burnbehaviour BS EN ISO 9239-1:2002	: Bfl-S1
Stairsuitability	: Yes
Widths	: 4 & 5 mtr +/-1 %
Cutlength service	: Yes
Standard rug sizes	: No
Bespoke rug service	: Yes

Matching: This sample may not be from the same batch as current stocks and should be used only as a guide.

Installation: Professional installation is recommended and essential to a good quality underlay. Avoid exposure direct sunlight. Areas that might receive prolonged exposure to direct sunlight should be protected by the use of blinds or curtains.

Maintenance: To maintain your carpets appearance it is recommended that it is vacuumed at least three times per week to remove particles of dirt and dust. It should be noted that overtime foot traffic will flatten the pile in main walkways causing areas of differential wear. This can cause the carpet to show areas of light and dark shading, this happens to all quality of velour carpets and would not be accepted as a basis for any complaint.

Cleaning: Professional cleaning is recommended, for help visit: www.highgradedcleaning.co.uk

ITC Natural Luxury Flooring
Schering 45
8281 JW Genemuiden
The Netherlands

T +31(0)38 38 611 60
F +31(0)38 38 611 61
E info@itcnaturalluxuryflooring.com
W www.itcnaturalluxuryflooring.com