

# ECO-VELVET

---

Construction	:	Hand Woven Velvet
Pile Material	:	100% Natural Undyed Wool
Secondary Backing	:	Cotton Cloth
Pile weight	:	ca. 2.50 kg/ sq mtr +/- 7.5% *
Total weight	:	ca. 3.20 kg / sq mtr +/- 7.5%
Carpet Thickness	:	ca. 14 mm +/- 1 mm
Usage Classification EN 1307:2014	:	Heavy Domestic / General Commercial
Comfort rating EN 1307:2014	:	LC 5
Static Electricity Charge	:	Anti static
Light ISO 105 B02:2013	:	5-6
Rubbing - Dry ISO 105 X12	:	4-5
Rubbing - Wet ISO 105 X12	:	4
Water ISO 105 E01 : 2013	:	5
TOG rating	:	1.74
Burn behaviour BS EN ISO 9239-1:2002	:	Bfl-S1
Stair suitability	:	Yes, domestic use
Widths	:	4 mtr & 5 mtr +/- 1%
Cut length service	:	Yes
Standard rug sizes	:	No
Bespoke rug service	:	Yes

**Construction:** This product is hand woven using un-dyed wool, small imperfections are possible, and as such add to the natural appearance of this product.

**Matching:** This sample may not be from the same dye batch as current stocks and should be used only as a guide. Equal matching between widths cannot be guaranteed.

**Installation:** Professional installation to a good quality underlay.

**Cleaning:** Professional cleaning recommended.

**Maintenance:** To maintain your carpets appearance, it is recommended that it is vacuumed at least three times a week.

It should be noted that overtime regular foot traffic will flatten the pile in main walkways, causing areas of differential wear. This can cause the carpet to show areas of light and dark shading, this happens to all quality velour carpets and would not be accepted as a basis for any complaint.

Fibre shedding is a normal characteristic of heavy quality wool which gets considerably reduced after initial usage.

\* Gross

ITC Natural Luxury Flooring  
Schering 45  
8281 JW Genemuiden  
The Netherlands

T +31(0)38 38 611 60  
F +31(0)38 38 611 61  
E [info@itcnaturalluxuryflooring.com](mailto:info@itcnaturalluxuryflooring.com)  
W [www.itcnaturalluxuryflooring.com](http://www.itcnaturalluxuryflooring.com)