

KENSINGTON

Construction	:	Tufted 1/8 cut pile
Pile Material	:	100% PA Solution Dyed Nylon – Stainmaster®
Secondary Backing	:	Luxury Backing
Pile weight	:	ca. 3.20 kg/ sq mtr +/- 7.5%
Total weight	:	ca. 3.90 kg/ sq mtr +/- 7.5%
Carpet Thickness	:	ca. 16 mm +/- 7.5 %
Usage Classification EN 1307:2014	:	Class 33 / Heavy Commercial use
Comfort rating EN 1307:2014	:	LC 5
Static Electricity Charge	:	Anti static
Light ISO 105 B02:2013	:	6
Rubbing - Dry ISO 105 X12	:	5
Rubbing - Wet ISO 105 X12	:	5
Water ISO 105 E01 : 2013	:	5
Water Stains EN1307/EN15115	:	5
TOG rating	:	1.63
Burn behaviour BS EN ISO 9239-1:2002	:	Bfl-S1
Stair suitability	:	Yes
Widths	:	4 mtr + 5 mtr Ex Stock +/- 1%
Cut length service	:	Yes
Standard rug sizes	:	No
Bespoke rug service	:	No

STAINMASTER
carpet®

Stainmaster® carpets feature fibre shield technology which is resistant to virtually any type of food and liquid spills. For a durable, attractive and easy to clean carpet for your home, business or even your yacht a Stainmaster® carpet is the perfect choice.

Matching: This sample may not be from the same dye batch as current stocks and should be used only as a guide. Equal matching between widths cannot be guaranteed.

Installation: Professional installation to a good quality underlay.

Cleaning: Professional cleaning recommended.

Maintenance: To maintain your carpets appearance, it is recommended that it is vacuumed at least three times a week. It should be noted that overtime regular foot traffic will flatten the pile in main walkways, causing areas of differential wear. This can cause the carpet to show areas of light and dark shading, this happens to all quality velour carpets and would not be accepted as a basis for any complaint.

ITC Natural Luxury Flooring
Schering 45
8281 JW Genemuiden
The Netherlands

T +31(0)38 38 611 60
F +31(0)38 38 611 61
E info@itcnaturalluxuryflooring.com
W www.itcnaturalluxuryflooring.com