

Victoria Twist (40oz)

Range	Solid	Heather
Suitability Domestic Suitability EN1307	Extra Heavy 33	Extra Heavy 33
Comfort Factor	5	5
Construction	Tufted Twist	Tufted Twist
Pile Fibre Content	80% Wool, 20% Polypropylene	80% Wool, 20% Polypropylene
Machine Gauge	39.37/10cm (1/10th)	31.5/10cm (1/8th)
Stitch Rate	45.3/10cm (11.5 S.P.I)	40.2/10cm (10.2 S.P.I)
Pile Weight	1356gms/m ² (40oz/yd ²)	1356gms/m ² (40oz/yd ²)
Total Carpet Weight	1916gms/m ² (56.51oz/yd ²)	1906gms/m ² (56.21oz/yd ²)
Pattern Repeat	N/A	N/A
Tuft Density	170,078/m ² (110/in ²)	126,504/m ² (81.6/in ²)
Pile Height	6.5mm (0.256")	7mm (0.278")
Total Thickness	8.5mm (0.335")	9mm (0.357")
Tog Rating	1.16	1.16
Primary Backing	Woven Polypropylene	Woven Polypropylene
Secondary Backing	LOC - weave®	LOC - weave®
Widths Available	4m (13'1") & 5m (16'5")	4m (13'1") & 5m (16'5")
Abrasion Resistance	In excess of 35,000 rubs	In excess of 25,000 rubs
Static Loading	88%	80%
CE Mark	EN14041: 2004 CLASS:Dfl-s1 SLIP: NPD	EN14041: 2004 CLASS:Dfl-s1 SLIP: NPD
Flammability Test Data	Low Radius Effects of Ignition	Low Radius Effects of Ignition
Light Fastness	5	5
Shampoo Fastness	4	4

This specification is correct at date of issue and details provided are accurate within expected tolerances.
Victoria Carpets Ltd. reserve the right to amend this specification without prior notice.