

QUALITY
ORDER CODE

DATE: **6/10/2017**
REPLACES: 9/08/2017

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

CASHMERE LUXE SMB
CSL

± 400 & 500
COLLECTION
5/64" VELVET

SOLUTION DYED

HALCYON 2-PLY PP

WOVEN

SMART BACK

± 1.720
± 2.690

± 12,5
± 15,0
± 272.160
± 50,40
± 54,00

±
±

± 30
PILE IN

✓
✓

NO SHOCK

Cl. 21
Domestic Moderate/Light



LC5



Efl



Heavy domestic / General non-domestic

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 25



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

±

THERMAL RETENTION

(±) m²/KW

ISO 8302

±

TOG rating

(±)

± 1,9

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

<

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SMB 400	CSL	SMB 500
150	WINTER BREEZE	150
230	BEACH WALK	230
250	CANDLE WICK	250
260	OYSTER BAY	260
430	SOFT TAUPE	430
820	EVENING SHADOW	820
830	WEST COAST GREY	830
860	SILVER SHINE	860
870	SEAGULL	870
880	MIST	880

SMB 400	CSL	SMB 500



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE