

QUALITY
ORDER CODE

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

DATE: 19/06/2018
REPLACES: 21/12/2010

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM ✓
LIVING ROOM ✓
OFFICE ✓
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE ✓
STAIRS PROFESSIONAL USE ✓
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING ✓
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

MAYFAIR VELVET SB
MFV

± 400 & 500
COLLECTION
1/10" SAXONY

PIECE DYED

WO
WOOLMARK
HEAVY DUTY RESIDENTIAL-MEDIUM DUTY CONTRACT ✓

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.365
± 2.550

± 6,6
± 8,8
± 200.940
± 39,40
± 51,00

±
±

± 25
PILE IN

✓
✓
✓

✓
✓

✓

CL. 23 - CL. 32
Domestic Heavy - Commercial General



LC5



Bfl-s1



Low radius

Heavy non-domestic

QUALITY

DIMENSIONAL STABILITY

EN 986

MAYFAIR VELVET SB

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

±

SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

±

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,136



TOG rating

(±)

± 1,36

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5-6

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 4

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01


≥ 4

WATERFASTNESS STAINING

ISO 105-E01

≥ 4

LABEL CE



RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SB/DL 400	MFV	SB/DL 500
0013	TULIPWOOD	0013
0093	AUBERGINE	0093
0110	CARMINE	0110
0123	CORAL	0123
0133	ROSE	0133
0163	MUSCAT	0163
0173	SALMON	0173
0220	ACORN	0220
0230	FLAX	0230
0250	MAGNOLIA	0250
0253	HARVEST	0253
0263	CAMEL	0263
0273	ALMOND	0273
0275	LIMESTONE	0275
0283	HAVANNA	0283
0383	BRONZE	0383
0422	CORNSTALK	0422
0432	BAMBOO MAT	0432
0673	PETROL	0673
0713	ATLANTIC	0713
0753	SKY	0753
0793	MIDNIGHT	0793
0803	EBONY	0803
0821	SLATE	0821
0830	ASH	0830
0843	MOONSHINE	0843
0850	MOONBEAM	0850

SB/DL 400	MFV	SB/DL 500
0870	SILVER	0870
0873	DOLPHIN	0873
0883	PEARL	0883

(30)

(30)



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE