

PRODUCT SPECIFICATION

BROCKWAY

THE HOME OF WOOL CARPET

DESCRIPTION	LAKELAND HERDWICK
SUITABLE FOR ALL AREAS OF THE HOME INC:	Class 33 Heavy Commercial use (BS EN 1307:2008)
PILE FIBRE CONTENT	100% PURE NEW WOOL
WIDTHS	4m + 5m
TOTAL PILE WEIGHT (gms/m2)	1559.4
TOTAL PILE WEIGHT (oz/yd2)	46
TOTAL CARPET WEIGHT (gms/m2)	2169.6
TOTAL CARPET WEIGHT (oz/yd2)	64
TOG RATING	1.3
CONSTRUCTION	Tufted Loop Pile
PRIMARY BACKING	Woven Polypropylene, Envirobac™
LAMINATE	EnviroBac Method (utilising polyolefins)
SECONDARY BACKING	Woven Polypropylene, Envirobac™
GAUGE (dcm)	5/32nd
GAUGE (inch)	25.20
TUFT DENSITY (sq dcm)	803.52
TUFT DENSITY (sq inch)	51.83
PILE HEIGHT ABOVE BACKING (mm)	6.5
PILE HEIGHT ABOVE BACKING (inch)	0.26
TOTAL THICKNESS (mm)	8.8
TOTAL THICKNESS (inch)	0.35
FLAMMABILITY RATING	Cfl -s1 (BS EN 13501-1:2018)
STATIC ELECTRICITY	No discomfort should be felt under normal conditions of temperature and humidity
COLOUR FASTNESS	Light, shampooing, dry and wet rub to the currently enforced Performance Rating Standards (ISO, EN, BS)
STATIC LOADING (Thickness loss after 24hrs recovery)	16.50%
DYNAMIC LOADING (per 1000 impacts)	1.2
LUXURY RATING (BS EN 1307: 2008)	LC4
PATTERN REPEAT	N/A